Smart Payment Terminal

SUNMI P3KH

Big-HD screen, Android payment terminal with physical keypad.










EXPRESS American Express
Certification

 \mathcal{G} EMVCo.

EMV Certification

AMERICAN



SUNMIUS





Future-proof product design.

An Android-powered POS terminal comes with the ultimate big screen and a classic keypad.

Futuristic metallic color. Slim body, only 18.5mm at its thinnest part.

Adaptable to various application scenario

A delicate keypad for the visually impaired with PIN brings an excellent user experience.

A one-stop payment solution built inside for worry-free transactions.

SUNMI OS: designed for payment and PCI & EMV certified security. TMS: deployed on a private cloud to securely manage your devices. RKI: inject or update keys with lower operating costs. Remote Assistance: remote troubleshooting for better service experience.



All-rounder, in all payment scenarios

Scan, tap, chip, swipe or customers can pay the way they like.









SUNMI P3 Family Application Scenario



Restaurant Ordering



Retail Inventory Counting & Checkout



Designed for the Visually Impaired

SUNMI P3KH Tech Specs

General Configuration

Drod	uct	Mo	اماء

T6831

Processor

Octa-Core, 4xA53 2.0GHz+4xA53 1 5GHz

os

SUNMI OS (Based on Android 11)

Memory

2GB RAM +32GB ROM

Display

5" HD,720*1280,IPS

Touch panel

Capacitive multi-touch

Printer

High-speed thermal printer: 70mm/s
Paper roll width/diameter: 58mm/40mm

Rear Camera

5MP AF,or 2M FF(Optional)

Front Camera

2MP FF Front camera (Optional)

Magstripe Reader

support 1/2/3 track,Bi-direction,complies with ISO7810/7811 standards

IC Card Reader

Support smart IC card, complies with ISO7816 standard

NFC Reader

Support TypeA&B card,Mifare card,complies ISO/IEC 14443,EMV, Paypass,Paywave

PSAM card slot

2xPSAM

SIM/SD Card Slot

1xSIM+1xMicro SD or 2xSIM,1xSIM+1xeSIM+ 1x Micro SD (Optional)

Network

2G&3G&4G

Wi-Fi

2.4G/5GHz,Supports IEEE 802.11 a/b/g/n/ac

Bluetooth

Bluetooth 5.0, support BLE

GPS

GPS,Glonass,Beidou, Galileo

G-Sensor

Optional

Buttons

1*Power Key

Keypad

15keys, '0'-'9' with number+alphabet,backlit

Speaker

1 speaker,90dB

Ports

1* Type-C USB OTG supported 6* Pogo pin on the back for charging/wired commucation (Optional)

Battery

Removable Lithium battery,7.7V/2630mAh

Power Adapter

Input: AC100-240V Output: 5V/2A

Dimensions(L*W*H)

201.4*80*18.5mm

Total Weight

415g minimum (include battery)

Environmental

Operating temperature: -10°C~50°C Storage temperature: -20°C~70°C

Cradle

Function Cradle, Support 1*USB-C,1*USB-A, 1*Ethernet (Optional), 1*RS232(Optional), WiFi(Optional)

^{*}The above scenarios apply to P3/P3KH/P3H.